




Jordan Petroleum Refinery Company

Material Safety Data Sheet

HD.IND.D.E, HS, HSX, T

NFPA: Flammability



JPRC LUB-21

HMIS III:

Flammability	1
Health	3
Reactivity	0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	HD.IND.D.E OIL 30, HD.IND.D.E OIL 40, HD.IND.D.E OIL T30, HD.IND.D.E OIL T40, HS20 SAE 30, HS20 SAE 40, HSX25 SAE 30, HSX25 SAE40.
MSDS Number:	JPRC LUB-21
Product Use Description:	<p>HD.IND.D.E Oil: Designed for the lubrication of medium-speed trunk-piston diesel engines, operating on residual fuels with sulfur contents below 3.0% wt.</p> <p>HS-20: HS-20 is intended for use in high speed diesel engines (including turbocharged engines), using distillate fuel with a sulfur content in the range of 1.00-1.25% wt, specially heavy-duty construction equipment like Caterpillar engines.</p> <p>HSX-25: Specifically designed for construction equipment working in severe conditions, and operated intensively with high sulfur content fuels in range of 1.25-1.5% wt sulfur.</p>
Company	<p>Jordan Petroleum Refinery</p> <p>Amman – Jordan.</p> <p>TEL: + 962 6 4630151 or 4657600</p> <p>FAX: + 962 6 4657934 or 4657939</p> <p>P.O.BOX: 3396 Amman 11181 – Jordan</p>

P.O.BOX: 1079 Amman 11118 – Jordan
Website: <http://www.jopetrol.com.jo>
E-mail: addeewan@jopetrol.com.jo

SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS.

COMPOSITION :	Base Oil GI
	Base Oil GII
	Additives (DI)
	PPD
	TBN Booster

SECTION 3. HAZARDS IDENTIFICATION

Hazardous identification

US OSHA hazard communication
standard for SN 500, SN 150,BS 150:

product assessed in accordance with
OSHA 29 CFR 1910.1200 & determined
to be hazardous

Effects of over exposure: no significant
effects expected.

Emergency response data: black semi –
solid. Dot ERG NO.- NA

SECTION 4. FIRST AID MEASURES

First Aid Measures:

Eye Contact

Flush thoroughly with water .If irritation
occurs , call a physician

Skin contact

Wash contact areas with soap & water.

Inhalation

Not expected to be a problem.

Ingestion

Not expected to be a problem when
ingested. If uncomfortable seek medical
assistance.

SECTION 5. FIRE-FIGHTING MEASURES

Fire- Fighting Measure

Extinguishing media:

Carbon dioxide, foam, dry chemical, and
water fog.

Special fire fighting procedures:

Water or foam may cause frothing. Use
water to keep fire exposed containers
cool. Water spray may be used to flush
spills away from exposure. Prevent runoff
from fire control or dilution from entering
streams, sewers, or drinking water
supply.

Special protective equipment:

For fires in enclosed areas, fire fighters
must use self-contained breathing
apparatus (SCBA) and full turnout gear.

Unusual fire and explosion hazards

Storage tank headspace may contain
flammable atmosphere.

NFPA hazard ID

Flammable limits- LEL: NA, UEL: NA.

Health : 3, Flammability : 1,

Reactivity : 0

Hazardous decomposition products

Carbon monoxide.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures

This material is slippery and might cause a traffic accident. If spilled on a road, it must be covered with sand immediately. In the event of a spill or leak, accident persons not wearing protective equipment and clothing should be restricted from contaminated areas until clean up has been completed.

The following steps should be undertaken following a spill or leak:

- 1- Notify safety personnel.
- 2- Remove all sources of heat and ignition.
- 3- Ventilate potentially explosive atmospheres.
- 4- Do not touch the spilled material; stop the leak if it is possible to do so without risk.
- 5- Use water spray to reduce vapors; do not get water inside container. Do not flush waste to sewers or open waterways.
- 6- For liquid spills, cover with sand and then remove for later disposal.
- 7- Prevent spills from entering storm sewers or drains.

Personal precautions

Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (see section 8). Follow all fire-fighting procedures.

SECTION 7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.

Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Store away from strong oxidizing agents or combustible material.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure controls/ personal protection

Respiratory protection	No special requirements under ordinary conditions of use and with adequate ventilation.
Skin and body	No special equipment required. However, good personal hygiene practices should always be followed.
Hands	Use chemical resistant apron and / or other clothing to protect against hot liquid & to avoid skin contact
Eyes	Normal industrial eye protection practices should be.
Engineering controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below there respective threshold limits value.
Occupational exposure limits	
Exposure limit of SN 500, BS 150, SN 150 for oil mist:	5.00 mg/m ³

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Appearance:	Bright and Clear,
VI for HD.IND.D.E 30:	103
VI for HD.IND.D.E 40:	103
VI for HS20 SAE 30:	103
VI for HS20 SAE 40:	103
VI for HSX25 SAE 30	104
VI for HSX25 SAE 40:	103
Flash point for HD.IND.D.E 30	245 ° C (COC)
Flash point for HD.IND.D.E 40:	250 ° C (COC)
Flash point for HS20 SAE 30:	245 ° C(COC)
Flash point for HS20 SAE 40:	250 ° C(COC)
Flash point for HSX25 SAE 30:	245 ° C(COC)
Flash point for HSX25 SAE 40:	250 ° C(COC)
Pour point for HD.IND.D.E 30:	-18 ° C
Pour point for HD.IND.D.E 40:	-18° C
Pour point for HS20 SAE 30:	-18° C
Pour point for HS20 SAE 40:	-18° C
Pour point for HSX25 SAE 30:	-18° C
Pour point for HSX25 SAE 40	-18° C

Density for HD.IND.D.E 30:	0.9028g/cm ³ @15°C Test Method: ASTM D 1298
Density for HD.IND.D.E 40:	0.9080 g/cm ³ @15°C Test Method: ASTM D 1298
Density for HS20 SAE 30:	0.8998 g/cm ³ @15°C Test Method: ASTM D 1298
Density for HS20 SAE 40:	0.9037 g/cm ³ @15°C Test Method: ASTM D 1298
Density for HSX25 SAE 30:	0.9025 g/cm ³ @15°C Test Method: ASTM D 1298
Density for HSX25 SAE 40:	0.9063 g/cm ³ @15°C Test Method: ASTM D 1298
Kinematic viscosity for HD.IND.D.E 30:	12centi-stock @ 40 °C Test Method ASTM D 445
Kinematic viscosity for HD.IND.D.E 40:	14.7enti-stock @ 100C Test Method ASTM D 445
Kinematic viscosity for HS20 SAE 30:	12 centi-stock @ 100C Test Method ASTM D 445
Kinematic viscosity for HS20 SAE 40:	14.7 centi-stock @ 100C Test Method ASTM D 445
Kinematic viscosity for HSX25 SAE 30:	11.5 centi-stock @ 100C Test Method ASTM D 445
Kinematic viscosity for HSX25 SAE 40:	14enti-stock @ 100C Test Method ASTM D 445
BN for HD.IND.D.E 30:	25 mg KOH/g
BN for HD.IND.D.E 40:	25 mg KOH/g
BN for HS20 SAE 30:	20 mg KOH/g
BN for HS20 SAE 40:	20 mg KOH/g
BN for HSX25 SAE 30:	25 mg KOH/g
BN for HSX25 SAE 40:	25 mg KOH/g
Sulfated Ash for HD.IND.D.E 30:	3.1 wt%
Sulfated Ash for HD.IND.D.E 40:	3.1 wt%
Sulfated Ash for HS20 SAE 30:	2.6 wt%
Sulfated Ash for HS20 SAE 40:	2.6 wt%
Sulfated Ash for HSX25 SAE 30:	3.1 wt%
Sulfated Ash for HSX25 SAE 40:	3.1 wt%

SECTION 10. STABILITY AND REACTIVITY

Stability:	The product is stable.
Material to avoid:	Strong oxidizing and reducing agents.
Condition to avoid:	High temperatures, sparks, and open flames.
Hazardous decomposition products:	Sulphur oxides. Hydrogen sulphide. Carbon monoxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Routes of Entry	Skin, Eyes, Ingestion, and Inhalation
Acute Effects	
Inhalation	Irritating to respiratory system.
Ingestion	Not determined.
Skin contact	Non-irritating to the skin.
Eye contact	Irritating to eyes.
LD ₅₀	>2000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Environmental Fate and effects: (SN 500, BS 150, SN 150)	This product is expected to be inherently biodegradable. There is no evidence to suggest bioaccumulation will occur. It is not expected to be toxic to aquatic organisms. Accidental spillage may lead to penetration in the soil and groundwater. However, there is no evidence that this would cause adverse ecological effects.
---	--

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal	Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be limited pursuant to the resource conservation and recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.
RCRA Information	The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40CFR, Part 261D), nor is not formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosively, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

SECTION 14. OTHER INFORMATION

LD ₅₀	Lethal Dose (mg/kg)
PEL	Permissible Exposure Limits
NFPA	National Fire Protection Association:

PPE
SCBA
TWA
OSHA

ACGIH

Personal Protective Equipment
Self – Contained Breathing Apparatus
Time – Weighted Average.
Occupational Safety And Health
Administration
American Conference of
Governmental Industrial Hygienists